

cleaner

UZIN VE 124

Alcohol-based epoxy thinners and gentle cleaning agent

Description and application:

Special thinners for solvent- and water-free two-component epoxy resins and as a gentle multipurpose cleaner-alcohol-based.

Suitable as thinners for:

- ▶ All UZIN 2-component epoxy flooring and tiling adhesives
- ▶ All UZIN 2-component epoxy primers

As well as for removing contamination from:

- ▶ Fresh, unset epoxy- and PU-reaction resin products and components
- ▶ Solvent-based resin adhesives and dried dispersion adhesives

Generally suitable for removing films of grease and oil from coverings, glass, metal, etc.

Properties/product advantages:

High solvent capacity for tacky, resinous, greasy and oily materials, e.g. reaction resin components, natural resins, plasticisers etc. Caution: may attack soft plastics.

Contains: Ethyl alcohol

- ▶ Highly flammable
- ▶ Thinners for epoxy resins
- ▶ Gentle solvent cleaning agent

Technical information:

Packaging:	plastic canister
Pack size:	5 litre
Shelf life:	min. 24 months
Colour:	colourless
Flash point:	16 °C / 61 °F



Application:

1. **As Thinners:** mix epoxy resin adhesive or primer. According to desired consistency add 5 - 10 % by weight of thinners and mix until homogenous. Even a small amount of thinners will produce a significantly thinner consistency and, for primers, increased penetration. Do not use for epoxy dispersions or for PU products.
2. **As a Cleaner:** to clean tools, put into a solvent-resistant box and place in the tools, brush etc. Allow to work, roughly clean and repeat with fresh thinners, if necessary several times. For surface cleaning, soak a rag with thinners and clean the soiled surface, if necessary repeat with fresh thinners several times. Soften dispersion adhesives with thinners, rinse with water and scrape off. Test objects and surfaces for solvent-resistance in advance.

Protection of the Workplace and the Environment:

High solvent content. Highly flammable. Solvents in this product may form explosive air-vapour mixture. Therefore provide good ventilation during and after use. No smoking, no open flames. Do not inhale vapours. Switch off all electric devices like doorbells, refrigerators, electric stoves, etc. Use barrier cream and protective gloves. Observe safety information on product label as well as safety data sheet.

Disposal

Where possible, collect product residues and re-use. Empty, drip-free containers are recyclable. Collected waste material and containers with liquid residues are special waste. Dispose properly according to local regulations. Highly flammable. Do not empty into drains, sewers or ground.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer. The publication of this Product Data Sheet invalidates all previous Product Information.

07.04 | 07.04 | 1.000 | Mar